



FlameGard® 5 UV/IR Flame Detector

Ultraviolet and infrared flame detection provides high immunity to false alarms

Description

The FlameGard 5 UV/IR Flame Detector is designed to detect fires and provide alarm outputs directly from the detector while maintaining false alarm immunity.

The FlameGard 5 UV/IR Flame Detector detects fires by monitoring in both the ultraviolet and infrared (UV & IR) spectral ranges, making it highly immune to false alarms caused by lightning, arc welding, hot objects and other sources of radiation.

Other features of the FlameGard 5 UV/IR Detector include three alarm/fault relays, and an RS-485 serial output with ModBus RTU protocol for linking up to 128 detectors in series or 247 with repeaters. The RS-485 and HART outputs provide status, alarm, fault and other information for operation, troubleshooting or programming of the units. HART enables this feature without the need for rewiring.

The continuous optical path monitoring (COPM) self test feature checks both the optical path integrity (window cleanliness) and the detector's electronic circuitry once every minute.



Features and Benefits

Wide field of view enables greater fire detection coverage

Event logging stores fault and alarm history

4-20 mA stepped output is the industry standard for remote alarm and fault indication

ModBus and HART user interface provides complete status and control capability in the control room

Wide operating temperature range permits operation at higher ambient temperature

Continuous Optical Path Monitoring (COPM) checks the optical path integrity and the detector's electronic circuitry once every minute

Three SPDT high-current programmable relay outputs provide immediate and time-delayed relay outputs for alarm, warning and fault conditions

Applications

- Aircraft Hangars
- Chemical Plants
- Compressor Stations
- Drilling and Production Platforms
- Electrostatic Paint Spray Booths
- Fuel Loading Facilities
- Gas Turbines
- LNG/LPG Processing and Storage Facilities

System Specifications

Wave Lengths	185 to 260 nm (UV) 4.35 microns (IR)
Field of View	120° max. conical
Sensitivity	Approved performance specifications – 50 feet (15.2m) distance for a 1 sq. ft (0.092m ²) heptane fire
Typical Response Time	< 3sec @ 50 ft.
Minimum Sensor Response Time	500 ms
Classification	Class I, Div 1 & 2, Groups B, C & D Class II, Div 1 & 2, Groups E, F & G Class III, Type 4X, Ex d IIC, T5, IP66
Warranty	Two years
Approvals	CSA, FM, ATEX, IECEx, HART registered, SIL 3 suitable, FM approved to IEC 61508
Standard Part Number	5 UVIR - 1513111 FlameGard 5 UVIR Flame Detector Single ModBus, Aluminum, 0-20mA Output, Relays, Aluminum Housing
Accessories	Mounting bracket, test lamp

Environmental Specifications

Operating Temperature Range	-40°F to +185°F (-40°C to +85°C)
Storage Temperature Range	-40°F to +185°F (-40°C to +85°C)
Operating Humidity Range	0% to 100% RH, non-condensing

Mechanical Specifications

Housing	Aluminum (stainless steel optional)
Length	5.5 inches (140 mm)
Diameter	6 inches (152 mm)
Weight	5 lbs (2.3 kg) – aluminum 16 lbs (7.3 kg) – stainless steel
Mounting	3/4" NPT (2 ports)
Cable Entry	2 x 3/4" NPT or 2 x 25 mm ISO or 2 x 20 mm ISO or 2 x 13.5 PG

Electrical Specifications

Input Power	20-36 VDC 24 VDC @ 150 mA max. (3.4 W max.)
Analog Signal	0 – 20 mA (600 Ohms maximum)
Fault Mode	0 – 0.2 mA*
COPM Fault	2 mA, ± 0.2 mA**
Ready Signal	4.05 mA, ± 0.05 mA
IR Signal	8 mA, +0.2 mA
UV Signal	20 mA, ± 0.2 mA
WARN Signal	8A @ 250 VAC, 8A @ 30 VDC resistive maximum
ALARM Signal	Complies with EN6100-6-4: 2001 and EN50130-4: 1995+A2: 2003
Relay Contact Rating	8A 250 VAC, 8A @ 30 VDC resistive (North America) 8A @ 30 VDC resistive (Europe)
Dip Switch Selectable Options	Sensitivity: 100%, 75%, 50% Alarm Time Delay: 2, 4, 8 or 10 seconds Warn & Alarm Relays: Latching/Non-latching Energized/De-energized
RS-485 Output	ModBus RTU, suitable for linking up to 128 units or up to 247 units with repeaters. Optional – Dual ModBus.
Baud Rate	2400, 4800, 9600, or 19200 BPS
HART (optional)	HART 6, HART Device Description Language available. AMS-aware
Wireless Communication	Available with ELPRO Technologies wireless devices
RFI /EMI Protection	Complies with EN 50130-4, EN 61000-6-4
Cable Requirements	Max. distance between detector and power source @ 24 VDC nominal (20 Ohm loop), 14 AWG – 4500 ft (1370 m) Terminal Blocks – 14-22 AWG
Status Indicator	2 LEDs with status, fault and alarm indication
Faults Monitored	Memory checksum, reset line shorted, optics failure / blockage, internal voltages, and low supply voltage

* Under HART, current values can be either 3.5 mA or 1.25 mA, depending on user selection

** Under HART, current value can be either 3.5 mA or 2.0 mA, depending on user selection

Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



MSA Corporate Center
1000 Cranberry Woods Drive
Cranberry Township, PA 16066 USA
Phone 724-776-8600
www.MSAnet.com
U.S. Customer Service Center
Phone 1-800-MSA-INST
Fax 1-800-967-0398

MSA Canada
Phone 1-800-MSA-INST
Fax 1-800-967-0398
MSA Mexico
Phone 01-800-672-7222
Fax 52-44 2227 3943
MSA International
Phone 724-776-8626
Toll Free 1-800-672-7777
FAX 724-741-1559

Offices and representatives worldwide
For further information:

